



Burroughs

SmartSource ReceiptNOW®



SmartSource
ReceiptNOW Elite



SmartSource
ReceiptNOW

Our Customers Say it Best!

“Integrating the ReceiptNOW printers and SmartSource scanners enabled us to deliver an enhanced client experience while capitalizing on processing efficiencies.” – *Rachel Emery, AVP Office Automation Manager, United Bank & Trust*

SmartSource ReceiptNOW

Prints receipts right at your check scanner. Engineered to fit under Burroughs SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

SmartSource ReceiptNOW — Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and other scanners.

SmartSource ReceiptNOW Elite — Engineered to fit beneath the SmartSource Elite series scanners.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

- Fast 8 inches/second (20 cm/second) delivery
- Less maintenance than matrix printers
- Fast installation for existing sites
- Three year warranty (advanced exchange available)

Compatibility

- USB or Ethernet (ReceiptNOW only) interface
- Full 108 std & international fonts w/barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

Customizable Teller Receipts

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper



SmartSource ReceiptNOW Technical Information



Models

- SRNELITE-USB – ReceiptNOW Elite, USB Interface
- SRN2PTR-USB – ReceiptNOW, USB Interface
- SRN2PTR-ETH – ReceiptNOW, Ethernet Interface

Printing/Feed/Cut

- Direct Thermal Printer
- Black and Two Color Capability
- Black Print Speed 8 inches/second (20 cm/second)
- Resolution: 203 x 180 dpi
- 95 Alphanumeric, 13 International Characters w/Kanji
- True Type Fonts available when being driven as a Windows printer
- 1D/2D Bar Code Fonts
- 512K on-board Logo Flash
- Full/Partial Auto Cutter

Controls

- On/Off Switch
- Paper Empty/Low LED's w/Audible Alerts
- Paper Feed Button
- Paper Width Adjustment
- Power indicator

Interface

- USB or 10/100 Base-T/TX
- Standard ESC/POS Command Set
- OPOS & JavaPOS, Auto Status Back (ASB)

Dimensions

	ReceiptNOW	ReceiptNOW Elite
Height:	5.4 inches (13.7 cm)	5.2 inches (13.2 cm)
Width:	15.3 inches (38.8 cm)	9.5 inches (24.2 cm)
Length:	6.1 inches (15.5 cm)	5.7 inches (14.5 cm)

Environment/Acoustics

- 5~50°C Operating Environment
- Acoustics < 60 dba Cutting or Printing



Power

- International Power 100-240VAC, 50/60Hz
- Power Supply Included

Paper/Loading

- Standard, Security, Non-BPA, 2-Color Paper
- 2.4 in. to 3.25 in. (6.1 cm to 8.3 cm) Paper Widths - Adjustable
- Largest 3.25 in. (8.3 cm) Diameter Paper Roll
- Slide Out Tray, Drop-in Paper

Warranty/Service

- 3 Year Warranty
- Advanced Exchange Available

Graphic Receipt Customization

- Multiple Graphics Can be Placed Anywhere
- Custom Messages
- Watermarks

Host OS

- Win 2000, XP, Vista (32/64), Windows 7 (32/64), Windows 8 (32/64)

Maintenance

- Print Exerciser & Diagnostic Software
- Operator Guide

Certifications

- FCC Class B, CE, VCCI, for EMI Emissions
- CE, for Susceptibility and ESD
- CE, CB, CUL/UL 60950, for Safety
- RoHS Compliant (EU)
- 2010 Appliance Efficiency Regulations, California, Title 20

For more information about the entire line of Burroughs remote capture products, call 1-800-BURROUGHS (1-800-287-7684) or visit www.burroughs.com

Burroughs is a registered trademark licensed to Burroughs, Inc. in the United States and other countries. SmartSource, ReceiptNOW and Cache2Cash are registered trademarks of Burroughs, Inc. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.



SmartTIP For more information use your smartphone and snap a photo.