



fi-6130/fi-6230

Color Duplex Workgroup Scanners

Discover a new level of front-office productivity with the fi-6130 and fi-6230 documents scanners

Enhanced with innovative features, the Fujitsu fi-6130 and fi-6230 scanners offer outstanding price/performance value in a compact footprint, conserving both space and budget. With duplex scanning performance of up to 80 images per minute in monochrome and grayscale, the fi-6130 and fi-6230 also delivers uncompromised high-resolution performance of up to 60 images per minute in color at an astounding 300 dpi. Engineered with one of the most advanced paper separation features in their class, the fi-6130 and fi-6230 are the first workgroup scanners equipped with reversing roller technology*, resulting in exceptional feeding reliability for an even wider variety of document weights. Furthermore, the automatic document feeder (ADF), capable of scanning document up to 10 feet long, is also robust enough to feed up to three hard cards continuously or an embossed card up to 1.4 mm in thickness. Additionally, the fi-6130 and fi-6230 harmoniously combines the security of Ultrasonic Double Feed Detection with the efficiency of Intelligent MultiFeed Function (iMFF) so that intentional double-feeds, such as a taped receipt or sticky note, can be manually bypassed while double-feed detection is enabled.

Fully Loaded One Box Solution

Fujitsu fi-6130 and fi-6230 workgroup scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all service programs, go to www.lmageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fuiltsu Computer Products of America, Inc., a subsidiary of Fuiltsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.

* Statement true as of March 2008







ADOBE ACROBAT 9 STANDARD





- Model fi-6130/fi-6230 Color Charge Coupled Device (CCD) x 2 Image Sensor Type fi-6130 Color Charge Coupled Device (CCD) x 3 fi-6230 Light Source White cold cathode discharge lamp Optical Resolution 600 dpi Color (24 bit) 50 to 600 dpi Output Resolution¹ Grayscale (8 bit) (adjustable by 1 dpi increments, 1200 dpi)2 Monochrome Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit Output Format AD Converter 1024 levels (10 bit) Output Mode Dither / Error diffusion Scanning Speeds Output (Letter/A4 size) Simplex Duplex 200 dpi 30 ppm 60 ipm 300 dpi 30 ppm 60 ipm 40 ppm 80 ipm Grayscale4 / 200 dpi Monochrome 60 ipm 300 dpi 30 ppm 50 Sheets (letter/A4, 20 lb.) ADF Capacity ADF minimum 2 in. x 3 in. (52mm x 74mm) ADF maximum 8.5 in. x 14 in. (Legal) Document size 8.4 in. x 122 in. (10 feet)9 Long document Flatbed (fi-6230 only) 8.5 in. x 11.69 in. (216mm x 297mm) 11 to 56.2 lb. (41 to 210g/m²) ADF Feeding Normal Paper Weight 34 to 56.2 lb. (127 to 210g/m²) A8 sheets (Thickness) Portrait and Landscape feeding8 Card⁶ (1 4mm) USB 2.0 / USB 1.1 (B type connector) Interface Physical Specifications Power requirements 100 - 240 VAC, 50/60 Hz fi-6130 38W or less (Sleep: less than 6.2W) Power consumption fi-6230 45W or less (Sleep: less than 6.2W) Dimensions fi-6130 11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm) 11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm) fi-6230 fi-6130 9.24 lb. (4.2 kg) Weight 19.36 lb. (8.8 kg) fi-6230 Environmental compatibility11 ENERGY STAR® and RoHS Operating Environment Temperature Relative humidity 42° to 95° F (5° to 35° C) 20% to 80% (non-condensing) Inbox Contents TWAIN, ISIS™, USB cable, AC adapter Adobe® Acrobat® Standard, **Bundled Software** Kofax® VRS® Professional and ScandAll Pro Options Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6230) Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) / OS Support Microsoft® Windows Server™ 2003 (32 bit/64 bit) / Microsoft® Windows Vista™ (32 bit/64 bit) Ultrasonic Double Feed Detection Sensor Feed Detection Features Intelligent Multifeed Function (Manual Bypass) Embossed and Hard Card Scanning Capability,Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background Other Features One-year. Advance Exchange program also available; restrictions apply. Limited Warranty For full details, visit www.lmagingService.com or call (800) 626-4686 Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, Service Options visit www.lmagingService.com or call (800) 626-4686.
- 1. Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
- 2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scan-
- 3. Actual scanning speeds are affected by data transmission and software processing times.

PA03540-B055

PA03540-B555

4 .IPEG compressed figures

Part Number

Technical Specifications

5. Maximum capacity varies, depending upon paper weight.

fi-6130

fi-6230

- 6. Supports ISO7810 embossed cards
- 7. Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
- 8. Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)
- 9. The scanning of documents that exceed 35 inches in length will be limited to using TWAIN at 200 dpi or less.
- 10. Excluding the ADF paper chute and stacker.
- 11. PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).

Fujitsu Computer Products of America, Inc.

http://us.fujitsu.com/fcpa 1250 East Argues Avenue Sunnyvale, CA 94085-4701 (800) 626-4686 (408) 746-7000 info@fcpa.fuiitsu.com



