

* The fi-6140/fi-6240 belongs to the class of A4 ADF color scanners whose scanning speeds meet or exceed 40 ppm / 80 ipm (color, A4, 200 dpi). This statement stood true as of October 2007.



fi-6140/fi-6240

High Performance Color **Duplex Scanners**

The Fujitsu fi-6140 and fi-6240 scanners bring high performance and advanced features in a compact design

In addition to the fi-6140 scanner being the smallest scanner in its class, both models are able to scan an impressive 60 pages or 120 images perminute in Monochrome or Grayscale (Letter @ 200dpi) as well as 40 pages or 80 images per-minute in Color (Letter @ 300dpi). Furthermore, the Fujitsu fi-6140 and fi-6240 models are the first scanners in their class to adopt high-end "fi series" functions such as:

- Paper Protection technology: Protects valuable documents by halting the scanning process when it recognizes that a jam is about to occur.
- Intelligent MultiFeed Function (iMFF): Simplifies pre-scanning preparation and improves efficiency by ignoring documents that trigger false multi-feed alerts such as an attached receipt or sticky note.
- Intelligent Capture Correction Function (iCCF): Auto-color recognition, autosize detection, and auto de-skew correction provides dramatic efficiency by combining fast scanning with simultaneous high speed image processing.

Along with ultrasonic double-feed detection, long document scanning (up to 10 feet), dual interfaces (ultra SCSI and USB 2.0), and embossed card scanning, these scanners can continuously feed up to 3 hard cards (up to 1.4 mm thick) through the Auto Document Feeder (ADF).

Fully Loaded One Box Solution

The Fujitsu fi-6140 and fi-6240 scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for the Fujitsu Advance Exchange Program, provides peaceof-mind. For full details on the Limited Warranty and on all Fujitsu service programs, go to www.lmageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.









fications						
Model		fi-6140/fi-6240				
Image Sensor Type fi-6140		Color Charge Coupled Device (CCD) x 2				
fi-6240		Color Charge Coupled Device (CCD) x 3				
Light Source		White cold cathode discharge lamp				
Optical Resolution		600 dpi				
Output Resolution ¹ Color (24 bi Grayscale (8						
		(aujustable by Lupi ilicitilitiits, 1200 upi)				
Output Format Monochrom		Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit				
AD Converter		1024 levels (10 bit)				
Scanning Speeds		1024 ICVCIS (10 BIT)				
Output (Letter/A4 size) ³		Simplex Duplex				
Color ⁴ 200 dp		40 ppm		80 ipm		
) dpi	40 pp	m	80 ipm		
200) dpi	60 pp	m	120 ipm		
Grayscale ⁴ / 200 Monochrome 300		40 pp	40 ppm 80 ipm			
ADF Capacity ⁵		50 Sheets (letter/A4, 20 lb.)				
		2 in. x 3 in. (52mm x 74mm)				
ADF maximum			8.5 in. x 14 in. (Legal)			
		only)	* * * * * * * * * * * * * * * * * * * *			
ADF Feeding Normal Paper Weight A8 sheets		11 to 56.2 lb. (41 to 210g/m²)				
		Portrait and Landscape feeding ⁸				
Interface ⁹ Physical Specifications			Ultra SCSI (50m) / Hi gh Speed USB 2.0			
	wuitohina)	1400	0.40.1/4.0. 50/00.11			
Power requirements (auto-switching)						
Power consumblion —		, ,				
_		11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)				
		,				
_		(0)				
compatibility						
perating Temperature						
Environment Relative humidi		,				
Inbox Contents		TWAIN, ISIS™, USB cable, AC adapter				
Bundled Software			Adobe® Acrobat® Standard,			
			Kofax® VRS® 4.x Professional and ScandAll Pro			
Options		Softv	Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6240)			
OS Support		Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) / Microsoft® Windows Server™ 2003 (32 bit/64 bit) / Microsoft® Windows Vista™ (32 bit/64 bit)				
Feed Detection Features			Ultrasonic Double Feed Detection Sensor Paper Protection Sensor Intelligent Multifeed Function			
Other Features			Ultrasonic Double Feed Detection, Intelligent Multi-Feed Function (iMFF), Paper Protection Function, Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only).			
Limited Warranty			One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.lmagingService.com or call (800) 626-4686.			
	Service Options			Post-Warranty: Advance Exchange Plus; restrictions apply.		
		Cons	umables: ScanAid TM kit. www.lmagingService.com 3540-B005	For full details,		
	ADF ma Flatbed Normal A8 shees Cards (1 father sheet of the father	Flatbed (fi-624C Normal A8 sheets Carde (1.4mm)? cations Its (auto-switching) fi-6140 fi-6240 fi-6140 fi-6240 fi-6240 mpatibility emperature elative humidity	ADF minimum ADF maximum Flatbed (fi-6240 only) Normal A8 sheets Card® (1.4mm)7 cations ats (auto-switching) 100 and fi-6140 42W fi-6240 11.8 fi-6140 11.8 fi-6140 19.24 fi-6240 19.3 mpatibility 19.24 representative humidity 20% TWA Adobt Kofa: Softv Micro Mic	ADF minimum 2 in. x 3 in. (52mm x 7 ADF maximum 8.5 in. x 14 in. (Legal) Flatbed (fi-6240 only) 8.5 in. x 14 in. (Legal) 11 to 56.2 lb. (41 to 21 A8 sheets 34 to 56.2 lb. (41 to 21 A8 sheets 34 to 56.2 lb. (127 to 21 A8 sheets 34 to 56.2 lb. (127 to 21 A8 sheets 34 to 56.2 lb. (127 to 22 Card® (1.4mm) Portrait and Landscape Ultra SCSI (50m) / Hi gli rations atts (auto-switching) 100 − 240 VAC, 50/60 Hz 16.6240 28 − 34 W, Energy saving more fi-6140 42W or less (Sleep: less than fi-6240 11.8 x 6.4 x 6.2 in. (301 x 16 fi-6240 11.8 x 22.9 x 9.0 in. (301 x 16 fi-6240 19.36 lb. (8.8 kg) mpatibility ENERGY STAR® and ROHS emperature 42° to 95° F (5° to 35° C) elative humidity 10 y60 kg Windows Server Microsoft® Windo		

- 1. Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner
- is scanning in simplex or duplex.
- 2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scan ning at high resolutions (600dpi or higher).
- 3. Actual scanning speeds are affected by data transmission and software processing times

PA03540-B505


- 4. JPEG compressed figures.
- 5. Maximum capacity varies, depending upon paper weight

fi-6240

- 6. Supports ISO7810 embossed cards
- 7. Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
- 8. Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)
- 9. Ultra SCSI interface cannot be used simultaneously with USB2.0
- 10. Excluding the ADF paper chute and stacker







http://us.fujitsu.com/fcpa 1250 East Argues Avenue Sunnyvale, CA 94085-4701 (800) 626-4686 (408) 746-7000 info@fcpa.fuiitsu.com



